



# M.D. STETSON

## ROYAL GLO FLOOR FINISH

Top of the line high-solid thermoplastic polymer blend fortified with urethane that produces a floor finish highly responsive to high speed buffing, including propane machines. **Royal Glo** Dries to a hard clear film, remarkably resistant to scuffing and black heel marking. **Royal Glo** is easy to-apply and maintain and will give exceptional protection, slip-resistance, and a brilliant shine. **Royal Glo** produces a three dimensional coating that responds to dry burnishing or further enhanced at any RPM when using a Stetson maintainer or restorer. A floor maintenance program encompassing a routine buffing operation will improve scuff, black-heel marking, and slip-resistance and extend the life of the finish while giving a brilliant gloss.

### DIRECTIONS FOR USE:

- Preparation:** Strip or scrub floor removing the desired amount of finish using a Stetson stripper or Winterclean for scrubbing. Thoroughly rinse the floor using Winterclean. Application of **Royal Glo** should be on completely clean floor.
- Optional:** If surface is in worn condition or porous, use **Royal Glo** or a Stetson sealer first to seal the floor.
- Application:** Do not dilute **Royal Glo**. Apply with a clean finish mop, microfiber pad or applicator, spreading evenly. Apply medium coats. If finish is to be maintained with a high speed buffing program, a base film of 4 to 6 coats of finish is recommended. Allow each coat to dry before applying the next coat. Application should not exceed more than 4 coats of finish in one day. Dry time will range from 20-45 minutes per coat depending on atmospheric conditions. On highly humid days extend dry times and reduce the number of coats applied per day.
  - Always wait 24 hours before buffing newly applied finish.
  - Never use a stripper or a high pH cleaner for routine maintenance.

### COVERAGE:

1500-3000 square feet, depending on the method of application and the porosity of the floor.

### PACKAGING:

Available in 1 gallon jugs, 5 gallon plastic pails, 30 and 55 gallon drums.

Refer to the material safety data sheet (MSDS) for detailed safety, health and environmental information.

### Maintenance:

- Sweep or dry mop floors on a daily basis.
- Damp mop or autoscrub with a Stetson neutral floor cleaner or a germicidal cleaner daily. Substitute Winterclean in the winter to remove de-icing salt residues.
- If a high speed buffing program is used, damp mop or autoscrub with one of Stetson's premium finish restorers prior to buffing. The result will be a sensational "wet look" gloss, increased slip-resistance, and an extended life for the finish.
- Worn or soiled areas can be recoated with 1 or 2 coats of **Royal Glo** as needed. Prior to application, scrub the floor with Winterclean using an autoscrubber or floor machine and the appropriate floor machine pad.

Please refer to Stetson's "Catch the Training" Strip & Refinish, Daily Floorcare or Scrub & Re-coat training guides for detailed instructions.

### SPECIFICATIONS:

Appearance .....	White emulsion
Solids.....	21% + 0.2
Pounds per gallon .....	8.60 + .05
Viscosity (Brookfield).....	2.65 + 0.15 cps
Gloss .....	Excellent
Levelling.....	Excellent
Crazing.....	None
Hazing.....	None
Water spot resistance	
1 hour .....	Very good
24 hours .....	Excellent



**Floor coating and finishing materials as to slip resistance only.**  
**3NRJ**

July 2011